

Certificate No: **TAE0000039** Revision No:

This is to certify:

That the Electric Power Cable

with type designation(s)
M2XH, M2XCH, M2XCH EMC

Issued to

Untel Kablolari San. ve Tic. A.S. Dilovasi, Turkey

is found to comply with

DNV GL rules for classification - Ships, offshore units, and high speed and light craft

Application:

General power and lighting.

Products approved by this certificate are accepted for installation on all vessels classed by DNV GL.

Type Rated voltage (kV) Temp. class (°C)

M2XH 0,6/1 kV 90 M2XCH 0,6/1 90 M2XCH EMC 0,6/1 90

Issued at Høvik on 2019-09-08

for **DNV GL**

This Certificate is valid until 2024-06-23.

DNV GL local station: Istanbul

Approval Engineer: Ivar Bull

Trond Sjåvåg Head of Section

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid. The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.



Form code: TA 251 Revision: 2016-12 www.dnvgl.com Page 1 of

Job Id: **262.1-008110-4** Certificate No: **TAE0000039**

Revision No: 3

Product description

Type: M2XH, M2XCH, M2XCH EMC 0,6/1 kV

Conductors: Plain or tinned stranded copper (class 2 or class 5)

Core insulation: Cross-Linked PolyEthylene (XLPE)

Option: Bedding/inner covering/filler

Bedding/Inner covering: Halogen free & flame retardant compound Filler: Flame retardant & non hygroscopic material

Braiding: Plain or tinned Copper wires (C Type)
EMC Screen: Electrolytic copper tape (EMC Type)
Outer sheath: Halogen Free Compound (SHF1)

No of cores:	Cross sectional area [mm ²]	
1	1 - 300	
2	1 - 25	
3	1 - 185	
4	1 - 120	
5	1 - 16	
7	1 1,5 2,5	
10, 12, 14, 16, 19, 24, 27, 37, 60	1,5	

Application/Limitation

The requirements of SOLAS Amendments Chapter II-1, Part D, Reg, 45, 5,2 (provision to be taken to limit Fire Propagation along Bunches of Cables or Wires) are fulfilled without any additional measures,

Type Approval documentation

Data sheets:

FR 70-022 Rev. 0 Rev. Tar. 01.09.2009. FR 70-023 Rev. 0 Rev. Tar. 01.09.2009. FR 70-024 Rev. 0 Rev. Tar. 01.09.2009.

Test reports: Untel test reports dated 11/10/2010

Tests carried out

	Release	General description	Limitation
DNVGL-CP-0399	2016-03	Class Programme Electric cables	
IEC 60092-350	2014-08	General construction and test methods of power, control and instrumentation cables for shipboard and offshore applications	
IEC 60092-360	2014-04	Electrical installations in ships - Part 360: Insulating and sheathing materials for shipboard and offshore units, power, control, instrumentation and telecommunication cables.	
IEC 60092-353	2016-09	Electrical installations in ships - Part 353: Power cables for rated voltages 1 kV and 3 kV	
IEC 60332-3-22	2018-07	Tests on electric cables under fire conditions - Part 3-22: Test for vertical flame spread of vertically-mounted bunched wires or cables - Category A	Charred portion of sample does not exceed 2,5m above bottom edge of burner.

Form code: TA 251 Revision: 2016-12 www.dnvgl.com Page 2 of 3

Job Id: **262.1-008110-4** Certificate No: **TAE0000039**

Revision No: 3

	Release	General description	Limitation
IEC 60754-1	2011-11	Test on gases evolved during combustion	Low Halogen:
		of materials from cables - Part 1:	<0,5% Halogen
		Determination of the halogen acid gas	
		content	
IEC 60754-2	2011-11	Test on gases evolved during combustion	Halogen free:
		of materials from cables - Part 2:	pH > 4,3
		Determination of acidity (by pH	Conductivity <
		measurement) and conductivity	10μS/mm
IEC 61034-1/2	2013-07	Measurement of smoke density of cables	Low smoke
	2013-09	burning under defined conditions –	Light
		Test apparatus, procedure and	transmittance >60%
		requirements	

Marking of product

ÜNTEL – M2XH or M2XCH or M2XCH EMC – size – IEC 60332 – Cat. A – 0,6/1 kV – Lot nr.

Periodical assessment

The scope of the periodical assessment is to verify that the conditions stipulated for the Type approval are complied with and that no alterations are made to the product design or choice of materials.

The main elements of the assessment are:

- Inspection on factory samples, selected at random from the production line (where practicable)
- Results from Routine tests (RT) and selected type tests (ref. to applicable class programs) checked (if not available these tests shall be carried out)
- Review of type approval documentation
- Review of possible change in design, materials and performance
- Ensuring traceability between manufacturer's product type marking and Type Approval Certificate.

Periodical assessment is to be performed after 2 years and after 3.5 years. A renewal assessment will be performed at renewal of the certificate.

END OF CERTIFICATE

Form code: TA 251 Revision: 2016-12 www.dnvgl.com Page 3 of 3